



Connectors 160/163 160 BU/ 2 DS NA

Order Info

| | |
|-----------------------------|---------------|
| reference number (ref. no.) | 151562 |
| PU | 250 |
| EAN | 4028012106783 |



Type

| | |
|-----------------|-----------|
| Type | socket |
| connection type | screw |
| number of poles | 2 pole |
| colour | naturalal |
| wire protection | yes |

Electrical Data

| | |
|-----------------------|--------|
| rated voltage | 400 V |
| rated current | 16 A |
| rated impulse voltage | 4.0 kV |

Connection Data

| | |
|---------------------------|--------------------------------|
| cross-section rating | 2.5 mm ² |
| cross-section rating (UL) | 14 AWG |
| clamping range | 0.5 - 2.5 mm ² |
| type of conductor | fine stranded, stranded, solid |
| stripping length | 6.5 - 7.0 mm |
| clamping units per pole | 1 |
| contact screw assembly | 0.6 x 3.5 / \cup 0.5 Nm |

Ambient Conditions

| | |
|---|-------|
| T _{max} ambient air (at rated current) | 70 °C |
| IP Code acc. to EN 60529 | IP20 |
| IP Code when plugged | IP40 |

Materials

| | |
|-----------------------------------|-------|
| insulator material | PA |
| contact material | brass |
| flammability rating acc. to UL 94 | V-2 |

Approvals