



Fused Terminal Blocks 503 SI/ 4 DS GW

Order Info

reference number (ref. no.)	19956
PU	200
EAN	4028012143863



Type

Type	screw terminal block with fuse holder 5x20
connection type	screw
number of poles	4 pole
colour	naturalal
wire protection	yes

Electrical Data

rated voltage	400 V
rated current	10 A

Connection Data

cross-section rating	2.5 mm ²
cross-section rating (UL)	22-12 AWG
clamping range	0.5 - 5.5 mm ²
type of conductor	fine stranded, stranded, solid
type of conductor internal	fine stranded, stranded, solid
type of conductor external	fine stranded, stranded, solid
stripping length	7.0 - 7.5 mm
clamping units per pole	1
contact screw assembly	0.8 x 4.0 / \cup 0.5 Nm
mounting hole diameter	3.1 mm
socket diameter	2.75 mm

Ambient Conditions

T _{max} ambient air (at rated current)	85 °C
T _{min} ambient air (operation)	-40 °C

Materials

insulator material	PA GW
contact material	brass

flammability rating acc. to UL 94	V-2
--	-----

Approvals

acc. to EN 60127	yes
-------------------------	-----

acc. to UL	yes
-------------------	-----

acc. to CSA	yes
--------------------	-----

Accessories

ZEL 110	196420
----------------	--------

ABK 503/ 4 GW	193814
----------------------	--------
