



## Lighting and Housing Connection IP66

### LCS 75/ 3-2

#### Order Info

reference number (ref. no.)	526232
PU	500
EAN	4028012134045



#### Type

Type	panel mount terminal block
connection type	push-in
number of poles	2 pole
colour	grey

#### Electrical Data

rated voltage	250 V
rated current	16 A
rated impulse voltage	2.0 kV

#### Connection Data

cross-section rating	2.5 mm <sup>2</sup>
clamping range	0.5 - 2.5 mm <sup>2</sup>
sheathing cable diameter	7.5 - 12.5 mm
type of conductor internal	solid
type of conductor external	fine stranded, stranded, solid
stripping length internal	12.0 mm
stripping length external	17.0 mm
dismantling length	60.0 mm
clamping units per pole	external: 1 / internal: 2
lock nut assembly	0.7 Nm
grommet assembly	0.7 Nm
housing hole	M20
pole marking	L N
wall thickness	0.5 - 2.5 mm

#### Ambient Conditions

T <sub>max</sub> ambient air (at rated current)	40 °C
T <sub>max</sub> component (operation)	70 °C
IP Code acc. to EN 60529	IP66

<b>ammonia resistance</b>	yes
---------------------------	-----

## Materials

<b>insulator material</b>	PA
---------------------------	----

<b>gasket material</b>	TPS
------------------------	-----

<b>contact material</b>	spring steel, copper
-------------------------	----------------------

## Approvals

<b>acc. to EN 60998</b>	yes
-------------------------	-----

## Accessories

<b>ABK 75/ 3</b>	526204
------------------	--------